



PRODUCT DATA SHEET



BEL-RAY[®] 2T MINERAL ENGINE OIL

Bel-Ray 2T Mineral Engine Oil is formulated from high quality mineral base stocks to provide clean burning performance and a high level of wear protection for all air-cooled or liquid-cooled scooter engines. It prevents ring sticking and spark plug fouling.

Applications

- ◆ For injector/autolube systems or premix in ratios recommended by the engine manufacturer, between 20:1 and 50:1
- ◆ Equally suitable for air-cooled or liquid-cooled engines
- ◆ For best performance and protection when operating over a wide temperature range under high rpm and high loads or at idling speeds

Features and Benefits

- | | |
|----------------------------|---|
| ◆ Superior anti-wear | Reduces cylinder and ring wear. Improves bearing life for longer engine service. |
| ◆ Superior deposit control | Cleans existing deposits. Reduces gum and varnish formation on pistons and ports. Keeps reed valves free of residue for improved throttle response over the entire power curve. Controls carbon deposits. |
| ◆ Superior combustibility | Low ash for cleaner burning. Eliminates spark plug fouling, pre-ignition and exhaust port plugging. |

General Description

Bel-Ray 2T Mineral Engine Oil gives the most cost-effective performance and protection with low ash Bel-Ray unique anti-wear and dispersant chemistry in a premium mineral base stock. It offers exceptional film strength for superior wear protection, improves ring seal for maximum compression and increases bearing life. Designed for today's high performance scooters, **Bel-Ray 2T Mineral Engine Oil** minimizes plug fouling and deposit build-up that can cause ring sticking, a major factor in engine failure and power loss.

Bel-Ray 2T Mineral Engine Oil is an API TC and JASO FB rated oil.

Product No. 99010

Page 1 of 2

6/1/2010

With continual research and development, Bel-Ray Company, Inc. reserves the right to change the information contained herein. The Company is not responsible for misuse or misapplication of its products.

BEL-RAY[®] 2T MINERAL ENGINE OIL

Product No. 99010

API Service Classification TC

JASO Performance Classification FB

Mixing Instructions

This product is formulated for a gas/oil injection or premix ratio ranging between 20:1 and 50:1. Follow the recommendation of the engine manufacturer.

<u>Fuel:Oil</u>	<u>½ gallon</u>	<u>1 gallon</u>	<u>1 liter</u>	<u>2 liters</u>	<u>3 liters</u>	<u>5 liters</u>
20:1	3.2oz	6.4oz	50cc	100cc	150cc	250cc
25:1	2.6oz	5.1oz	40cc	80cc	120cc	200cc
28:1	2.3oz	4.5oz	36cc	71cc	107cc	179cc
32:1	2.0oz	4.0oz	31cc	63cc	94cc	156cc
40:1	1.5oz	3.0oz	25cc	50cc	75cc	125cc
45:1	1.4oz	2.8oz	22cc	44cc	67cc	111cc
50:1	1.3oz	2.6oz	20cc	40cc	60cc	100cc